Texochem Industries

TECHNICAL DATASHEET

Texobond 1040

General

Texobond 1040 is an acrylic emulsion-based pressure sensitive adhesive. It has very high tack and good cohesive strength to provide non transfer properties. Texobond 1040 provides high green strength along with good shear strength. It can be used for bonding variety of substrate materials ranging from plastic sheets, foam pads, metallic components, wood, and rubber components.

Typical Properties

Appearance	Milky white paste
% Solids	54 ± 2%
pH	7.0 – 9.0
Tack	1500 – 2000 gf

Advantages

- Excellent adhesion to a variety of surfaces
- Uniform particle size distribution to ensure smooth coating
- Adjustable viscosity as per application
- Ecofriendly and VOC compliant
- Easy to clean from machine rolls

Our recommendations, if any, for use of this product are based on tests believed to be reliable. The greatest care is exercised in the selection of our materials and in our manufacturing operations. However, we make no recommendation to use this product in any manner which conflicts with existing laws and/or patents and we make no warranties, express or implied, regarding this product or its use, including merchantability and fitness for particular purpose. The manufacturer is not liable for any consequential, incidental, or special damages of any kind. We encourage customers to perform their own tests to confirm performance of the product.

Texochem Industries: A-714 TTC Industrial Area, MIDC, Mahape, Navi Mumbai – 400710.

www.texochem.com