Texochem Industries

TECHNICAL DATASHEET

Texobond 4560

General

Texobond 4560 is an acrylic emulsion-based pressure sensitive adhesive with low tack properties. It is commonly used in protective films, repositionable adhesives, and removable adhesives. Its high cohesive strength prevents any adhesive transfer and allows for clean release.

Typical Properties

Appearance	White milky emulsion
% Solids	56 ± 2%
pH	7.0 – 9.0
Viscosity	40 – 60 Poise

Advantages

- Soft polymer with smooth release
- Leaves no adhesive residue
- Can be used on variety of surfaces
- Maintains low adhesive strength throughout its life. Adhesion does not increase over time.
- Easy to apply and clean from machine rolls
- Ecofriendly and zero VOC product

Our recommendations, if any, for use of this product are based on tests believed to be reliable. The greatest care is exercised in the selection of our materials and in our manufacturing operations. However, we make no recommendation to use this product in any manner which conflicts with existing laws and/or patents and we make no warranties, express or implied, regarding this product or its use, including merchantability and fitness for particular purpose. The manufacturer is not liable for any consequential, incidental, or special damages of any kind. We encourage customers to perform their own tests to confirm performance of the product.

Texochem Industries: A-714 TTC Industrial Area, MIDC, Mahape, Navi Mumbai – 400710.

www.texochem.com